

RESOPAL® BUILDING ENVIRONMENTAL DATA SHEET






 NEW CONSTRUCTION

 REFURBISHMENT

COMPACT HPL - RESOPAL® COMPACT INTERIOR FITTING

International Non-Domestic Refurbishment 2015 (SD225 1.4)
Office (O) - Retail (R) - Hospitality (Ho)

The technical scheme of the certification encompasses the requirements relating to the project itself (its implementation, function, architectural design, etc.) and to the materials, products and equipment within it. Depending on the certification, the table below shows how RESOPAL Compact fulfils the requirements and with which level of performance. The following pages outline each of the requirements, and detail how RESOPAL Compact is affected and meets them. At the end of the document you will find a clickable link allowing access to the documentation proofs.

Section	Issue	Criterion - RESOPAL product contribution	Points
 HEA Health and Well-Being	Hea 01 Visual Comfort	Daylighting Product eases natural lighting	Up to 3 pts
 MAT Materials	Mat 01 Environmental Impact of Materials	Option 1: Project life cycle assessment study Mastering the environmental impact	Up to 6 pts
		Option 2: Elemental assessment of environmental performance information Product with conforming life cycle analysis	Up to 4 pts
 MAT Materials	Mat 03 Responsible Sourcing of Materials	Legal timber-based products Wood environmental certifications	Prerequisite
		Responsible sourcing of construction products Product sourced responsibly	Up to 3 pts
 INN Innovation	Inn 01 Innovation	Exemplary level of performance Earn exemplary performance points with RESOPAL Compact	Up to 4 pts

Hea 01 - Visual Comfort



Criterion	Requirement - RESOPAL product contribution - Documentation	
Daylighting	RESPECT A CERTAIN DAYLIGHT FACTOR (DF) PERCENTAGE FOR A MINIMUM SURFACE AREA IN THE PROJECT.	
	Up to 3 pts	<p>Product eases natural lighting</p> <p>Indirect influence: The daylight factor calculation takes account of different factors including the light reflectance value of floors, walls and ceilings.</p> <p>With its large range of over 300 decors (plain, wood, materials), RESOPAL Compact contributes to obtaining excellent daylight factor percentages: Its light reflectance values range from 0.06 for the 0901 Black decor to 0.85 for the 9417 Snow White decor.</p> <ul style="list-style-type: none"> • Data Sheet - Surface Gloss and Surface Brightness - EN

Mat 01 - Environmental Impact of Materials



Criterion	Requirement - RESOPAL product contribution - Documentation	
Option 1 - Project life cycle assessment study	CARRY OUT AN LCA TO GAUGE THE ENVIRONMENTAL IMPACT OF THE LIFE CYCLE OF RENOVATION OR CONSTRUCTION WORK.	
	Up to 6 pts	<p>Product with conforming life cycle analysis</p> <p>Indirect influence: Wall and ceiling coverings are among the obligatory elements to be included in the environmental impact calculation of the project.</p> <p>RESOPAL carries out Life Cycle Analysis (LCA) for its products and supplies the environmental product declarations required for this calculation.</p> <ul style="list-style-type: none"> • Environmental Product Declaration (EPD) - EN • Environmental Product Declaration (EPD) - background information - EN
Option 2 - Elemental assessment of environmental performance information	HAVE THE RELEVANT ENVIRONMENTAL INFORMATION ON NEW PRODUCTS USED.	
	Up to 4 pts	Identical to option 1.



Mat 03 - Responsible Sourcing of Materials

Criterion	Requirement - RESOPAL product contribution - Documentation	
Legal timber-based products	ENSURE THAT THE WOOD USED IN PRODUCTS IS LEGALLY SOURCED.	
	Prerequisite	<p>Wood environmental certifications</p> <p>Indirect influence: All our products can be either PEFC (PEFC/04-31-1353) or FSC® (TSUD-COC-001239 and TSUD-CW-001239) certified on request, guaranteeing that the wood and raw materials used come from sustainably and responsibly managed forests (depending on the certification of our suppliers, while stocks last). NOTE: this criterion is also a prerequisite for the MAT03 - Responsible construction practices issue.</p> <ul style="list-style-type: none"> • PEFC-Certificate - EN • FSC®-Certificate - EN • Declaration European Timber Regulation (EUTR) - EN
Responsible Sourcing of Materials (RSM)	USE PRODUCTS SOURCED FROM A RESPONSIBLE SECTOR.	
	Up to 3 pts	<p>Product sourced responsibly</p> <p>Direct influence: All our products can be either PEFC (TSUD-PEFC-COC-000086) or FSC® (TSUD-COC-001239 and TSUD-CW-001239) certified on request, guaranteeing that the wood and raw materials used come from sustainably and responsibly managed forests (depending on the certification of our suppliers, while stocks last).</p> <ul style="list-style-type: none"> • PEFC-Certificate - EN • FSC®-Certificate - EN



Inn 01 - Innovation

Criterion	Requirement - RESOPAL product contribution - Documentation																																				
Exemplary level of performance	FULFIL REINFORCED REQUIREMENTS ON SOME CRITERIA FROM OTHER SECTIONS.																																				
	Up to 4 pts	Volatile organic compound (VOC) emission levels (products)	Up to 2 pts	Among the criteria that earn exemplary performance points, three concern RESOPAL Compact.																																	
				Hea 02 - Indoor Air Quality (1 to 2 pts)																																	
				<p>Product with very low TVOC and formaldehyde emissions</p> <p>Direct influence: RESOPAL Compact is a low-emitting material confirmed by a third-party testing institute. RESOPAL Compact complies with the strictest requirements in terms of indoor air quality, in accordance with the emissions criteria used by the United States Environmental Protection Agency (EPA), the State of California, the German Blue Angel (Blauer Engel) certification and other internationally known public health agencies.</p>																																	
				<table border="1"> <thead> <tr> <th rowspan="2"></th> <th rowspan="2">Regulation</th> <th colspan="2">TVOC</th> <th colspan="2">Formaldehyde</th> </tr> <tr> <th colspan="4">MAXIMUM CONCENTRATIONS (µg/m³) - MEASURED AFTER 28 DAYS</th> </tr> <tr> <th></th> <th></th> <th>limit</th> <th>value</th> <th>limit</th> <th>value</th> </tr> </thead> <tbody> <tr> <td>RESOPAL Compact WALL SCENARIO</td> <td>ABG/AgBB</td> <td>≤ 1000</td> <td>< 5</td> <td>≤ 100</td> <td>24</td> </tr> <tr> <td>RESOPAL TRACELESS PREMIUM Compact ALL SCENARIOS</td> <td>ABG/AgBB</td> <td>≤ 1000</td> <td>< 5</td> <td>≤ 100</td> <td>< 3</td> </tr> <tr> <td>RESOPAL Compact DOOR SCENARIO</td> <td>ABG/AgBB</td> <td>≤ 1000</td> <td>< 5</td> <td>≤ 100</td> <td>< 3</td> </tr> </tbody> </table>			Regulation	TVOC		Formaldehyde		MAXIMUM CONCENTRATIONS (µg/m³) - MEASURED AFTER 28 DAYS						limit	value	limit	value	RESOPAL Compact WALL SCENARIO	ABG/AgBB	≤ 1000	< 5	≤ 100	24	RESOPAL TRACELESS PREMIUM Compact ALL SCENARIOS	ABG/AgBB	≤ 1000	< 5	≤ 100	< 3	RESOPAL Compact DOOR SCENARIO	ABG/AgBB	≤ 1000	< 5
	Regulation	TVOC		Formaldehyde																																	
		MAXIMUM CONCENTRATIONS (µg/m³) - MEASURED AFTER 28 DAYS																																			
		limit	value	limit	value																																
RESOPAL Compact WALL SCENARIO	ABG/AgBB	≤ 1000	< 5	≤ 100	24																																
RESOPAL TRACELESS PREMIUM Compact ALL SCENARIOS	ABG/AgBB	≤ 1000	< 5	≤ 100	< 3																																
RESOPAL Compact DOOR SCENARIO	ABG/AgBB	≤ 1000	< 5	≤ 100	< 3																																
		<p>NOTE: French VOC labelling</p> <p>In the framework of the French VOC label, Resopal measures VOC emissions from its products in accordance with the ISO 16000 standard. RESOPAL Compact has received the following classification:</p>																																			
		<table border="1"> <thead> <tr> <th rowspan="2"></th> <th rowspan="2">Classification</th> <th colspan="2">TVOC</th> <th colspan="2">Formaldehyde</th> </tr> <tr> <th colspan="4">MAXIMUM CONCENTRATIONS (µg/m³) - MEASURED AFTER 28 DAYS</th> </tr> <tr> <th></th> <th></th> <th>limit</th> <th>value</th> <th>limit</th> <th>value</th> </tr> </thead> <tbody> <tr> <td>RESOPAL Compact WALL SCENARIO</td> <td>A</td> <td>< 1500</td> <td>< 2</td> <td>< 60</td> <td>24</td> </tr> <tr> <td>RESOPAL TRACELESS PREMIUM Compact ALL SCENARIOS</td> <td>A+</td> <td>< 1000</td> <td>< 2</td> <td>< 10</td> <td>< 3</td> </tr> <tr> <td>RESOPAL Compact DOOR SCENARIO</td> <td>A+</td> <td>< 1000</td> <td>< 2</td> <td>< 10</td> <td>< 3</td> </tr> </tbody> </table>			Classification	TVOC		Formaldehyde		MAXIMUM CONCENTRATIONS (µg/m³) - MEASURED AFTER 28 DAYS						limit	value	limit	value	RESOPAL Compact WALL SCENARIO	A	< 1500	< 2	< 60	24	RESOPAL TRACELESS PREMIUM Compact ALL SCENARIOS	A+	< 1000	< 2	< 10	< 3	RESOPAL Compact DOOR SCENARIO	A+	< 1000	< 2	< 10	< 3
	Classification	TVOC				Formaldehyde																															
		MAXIMUM CONCENTRATIONS (µg/m³) - MEASURED AFTER 28 DAYS																																			
		limit	value	limit	value																																
RESOPAL Compact WALL SCENARIO	A	< 1500	< 2	< 60	24																																
RESOPAL TRACELESS PREMIUM Compact ALL SCENARIOS	A+	< 1000	< 2	< 10	< 3																																
RESOPAL Compact DOOR SCENARIO	A+	< 1000	< 2	< 10	< 3																																
		<ul style="list-style-type: none"> • VOC Emission test report - Wall - RESOPAL Compact - EN • VOC Emission test report - Door - RESOPAL Compact - EN • VOC Emission test report - Wall - RESOPAL Compact Traceless Premium - EN 																																			
		Mat 01 (1pt) : When the maximum score is reached in the LCA tool.																																			
		Mat 03 (1pt) : When more products are sourced responsibly.																																			

Download all documentation proofs here

