

RESOPAL® BUILDING ENVIRONMENTAL DATA SHEET







 NEW CONSTRUCTION

 REFURBISHMENT

MELAMINE-FACED BOARD - RESOPAL® MFB INTERIOR FITTING

International New Construction 2016 (SD233 2.0)
Office (O) - Retail (R) - Hospitality (Ho) - Healthcare (He)

The technical scheme of the certification encompasses the requirements relating to the project itself (its implementation, function, architectural design, etc.) and to the materials, products and equipment within it. Depending on the certification, the table below shows how RESOPAL MFB¹ fulfils the requirements and with which level of performance. The following pages outline each of the requirements, and detail how RESOPAL MFB is affected and meets them. At the end of the document you will find a clickable link allowing access to the documentation proofs.

Section	Issue	Criterion - RESOPAL product contribution	Points
 HEA Health and Well-Being	Hea 01 Visual Comfort	Daylighting Product eases natural lighting	O: 1 pt R: 2 pts Ho: 1 pt
	 Hea 02 Indoor Air Quality	Emissions from building products Product with very low TVOC and formaldehyde emissions	1 pt
 MAT Materials	Mat 01 Life Cycle Impacts	Life Cycle Assessment (LCA) Product with conforming life cycle analysis	Up to 5 pts
	 Mat 03 Responsible Sourcing of Construction Products	Environmental Product Declarations (EPD) Voluntary environmental product declaration by an independent organisation	1 pt
		Legal timber-based products Wood environmental certifications	Prerequisite
 INN Innovation	Inn 01 Innovation	Responsible sourcing of construction products Product sourced responsibly	Up to 3 pts
		Exemplary level of performance Earn exemplary performance points with RESOPAL MFB	Up to 2 pts

¹ All data in this data sheet refers exclusively to RESOPAL MFB and does not apply to RESOPAL Resopalit.

Hea 01 - Visual Comfort



Criterion	Requirement - RESOPAL product contribution - Documentation	
Daylighting	RESPECT A CERTAIN DAYLIGHT FACTOR (DF) PERCENTAGE FOR A MINIMUM SURFACE AREA IN THE PROJECT.	
	O: 1 pt R: 2 pts Ho: 1 pt	<p>Product eases natural lighting</p> <p>Indirect influence: The daylight factor calculation takes account of different factors including the light reflectance value of floors, walls and ceilings.</p> <p>With its large range of over 300 decors (plain, wood, materials), RESOPAL MFB contributes to obtaining excellent daylight factor percentages: Its light reflectance values range from 0.06 for the 0901 Black decor to 0.85 for the 9417 Snow White decor.</p> <ul style="list-style-type: none"> • Data Sheet - Surface Gloss and Surface Brightness - EN

Hea 02 - Indoor Air Quality



Criterion	Requirement - RESOPAL product contribution - Documentation																														
Emissions from building products	USE PRODUCTS WHOSE EMISSION LEVELS RESPECT CERTAIN THRESHOLDS: FORMALDEHYDE < 60 µg/m ³ , TVOC < 1000 µg/m ³ AND 1A AND 1B CARCINOGENIC SUBSTANCES < 1 µg/m ³ .																														
	1 pt	<p>Product with very low TVOC and formaldehyde emissions</p> <p>In the framework of the French VOC label, Resopal measures VOC emissions from its products in accordance with the ISO 16000 standard. RESOPAL MFB has received the following classification:</p>																													
		<table border="1"> <thead> <tr> <th></th> <th colspan="2">TVOC</th> <th colspan="2">Formaldehyde</th> </tr> <tr> <th></th> <th colspan="4">MAXIMUM CONCENTRATIONS (µg/m³) - MEASURED AFTER 28 DAYS</th> </tr> <tr> <th></th> <th>limit</th> <th>value</th> <th>limit</th> <th>value</th> </tr> </thead> <tbody> <tr> <td>RESOPAL MFB CHIPBOARD - STANDARD QUALITY</td> <td>< 1000</td> <td>190 µg/m³</td> <td>A+</td> <td>< 10</td> <td>8.6 µg/m³</td> <td>A+</td> </tr> <tr> <td>RESOPAL TRACELESS FACED BOARD</td> <td>< 1000</td> <td>140 µg/m³</td> <td>A+</td> <td>< 60</td> <td>46 µg/m³</td> <td>A</td> </tr> </tbody> </table>		TVOC		Formaldehyde			MAXIMUM CONCENTRATIONS (µg/m ³) - MEASURED AFTER 28 DAYS					limit	value	limit	value	RESOPAL MFB CHIPBOARD - STANDARD QUALITY	< 1000	190 µg/m ³	A+	< 10	8.6 µg/m ³	A+	RESOPAL TRACELESS FACED BOARD	< 1000	140 µg/m ³	A+	< 60	46 µg/m ³	A
			TVOC		Formaldehyde																										
	MAXIMUM CONCENTRATIONS (µg/m ³) - MEASURED AFTER 28 DAYS																														
	limit	value	limit	value																											
RESOPAL MFB CHIPBOARD - STANDARD QUALITY	< 1000	190 µg/m ³	A+	< 10	8.6 µg/m ³	A+																									
RESOPAL TRACELESS FACED BOARD	< 1000	140 µg/m ³	A+	< 60	46 µg/m ³	A																									
<ul style="list-style-type: none"> • VOC Emission test report - RESOPAL MFB - EN • VOC Emission test report - RESOPAL Traceless Faced Board - EN 																															



Mat 01 - Life Cycle Impacts

Criterion	Requirement - RESOPAL product contribution - Documentation	
Life Cycle Assessment (LCA)	CALCULATE THE ENVIRONMENTAL IMPACT OF THE BUILDING THROUGH A LIFE CYCLE ANALYSIS INCLUDING AT LEAST CERTAIN PRODUCTS.	
	Up to 5 pts	<p>Product with conforming life cycle analysis</p> <p>Indirect influence: Wall and ceiling coverings are among the obligatory elements to be included in the environmental impact calculation of the project. RESOPAL carries out Life Cycle Analysis (LCA) for its products and supplies the environmental product declarations required for this calculation.</p> <ul style="list-style-type: none"> • FDES - RESOPAL MFB - Qualité Standard - FR • FDES - RESOPAL MFB - Qualité Hydrofuge - FR • EPD - RESOPAL MFB - Standard Quality - EN • EPD - RESOPAL MFB - Moisture-Resistant Quality - EN
Environmental Product Declarations (EPD)	INSTALL A CERTAIN NUMBER OF PRODUCTS WITH COMPLIANT ENVIRONMENTAL PRODUCT DECLARATIONS.	
	1 pt	<p>Voluntary environmental product declaration by an independent organisation</p> <p>Direct influence: RESOPAL has carried out Life Cycle Analysis (LCA) for RESOPAL MFB in compliance with the DIN EN 15804:2012+A1:2014 standard.</p> <ul style="list-style-type: none"> • FDES - RESOPAL MFB - Qualité Standard - FR • FDES - RESOPAL MFB - Qualité Hydrofuge - FR • EPD - RESOPAL MFB - Standard Quality - EN • EPD - RESOPAL MFB - Moisture-Resistant Quality - EN



Mat 03 - Responsible Sourcing of Construction Products

Criterion	Requirement - RESOPAL product contribution - Documentation	
Legal timber-based products	ENSURE THAT THE WOOD USED IN PRODUCTS IS LEGALLY SOURCED.	
	Prerequisite	<p>Wood environmental certifications</p> <p>RESOPAL MFB:</p> <ul style="list-style-type: none"> - 85% composed of an anhydrous wood core from the following sources: 20% roundwood (twigs, branches, downgraded logs), 37% related products (chips, particles) from other wood-working industries (sawmills, joineries, furniture makers, etc.), 43% secondary raw materials for recycling (chips from wood waste shredding). - All our products can be either PEFC (PEFC/04-31-1353) or FSC® (TSUD-COC-001239 and TSUD-CW-001239) certified on request, guaranteeing that the wood and raw materials used come from sustainably and responsibly managed forests (depending on the certification of our suppliers, while stocks last). <p>It is therefore included in the calculation of the volume of wood used in the structure, with reference to the order of 13 September 2010 establishing the method for calculating the volume of wood used in certain constructions.</p> <ul style="list-style-type: none"> • PEFC-Certificate - EN • FSC®-Certificate - EN • Declaration European Timber Regulation (EUTR) - EN
Responsible sourcing of construction products	CONTAIN A CERTAIN PERCENTAGE OF PRODUCTS SOURCED FROM A RESPONSIBLE CHANNEL: THE NUMBER OF POINTS OBTAINED DEPENDS ON THIS PERCENTAGE VALUE.	
	Up to 3 pts	<p>Product sourced responsibly</p> <p>Direct influence: All our products can be either PEFC (TSUD-PEFC-COC-000086) or FSC® (TSUD-COC-001239 and TSUD-CW-001239) certified on request, guaranteeing that the wood and raw materials used come from sustainably and responsibly managed forests (depending on the certification of our suppliers, while stocks last).</p> <ul style="list-style-type: none"> • PEFC-Certificate - EN • FSC®-Certificate - EN



Inn 01 - Innovation

Criterion	Requirement - RESOPAL product contribution - Documentation	
Exemplary level of performance	FULFIL REINFORCED REQUIREMENTS ON SOME CRITERIA FROM OTHER SECTIONS.	
	Up to 2 pts	<p>Earn exemplary performance points with RESOPAL MFB</p> <p>Among the criteria that earn exemplary performance points, two concern RESOPAL MFB:</p> <p>Mat 01 (1 pt): When the maximum score is reached in the LCA tool.</p> <p>Mat 03 (1 pt): When more products are sourced responsibly.</p>

Download all documentation proofs here

