RESOPAL® BUILDING ENVIRONMENTAL DATA SHEET



REFURBISHMENT

COMPACT HPL - RESOPAL® COMPACT INTERIOR FITTING

LEED v4 - Interior Design and Construction (ID+C) Office (O) - Retail (R) - Hospitality (Ho)

The technical scheme of the certification encompasses the requirements relating to the project itself (its implementation, function, architectural design, etc.) and to the materials, products and equipment within it. Depending on the certification, the table below shows how RESOPAL Compact fulfils the requirements and with which level of performance. The following pages outline each of the requirements, and detail how RESOPAL Compact is affected and meets them. At the end of the document you will find a clickable link allowing access to the documentation proofs.

Credit category		Credit	Requirement - RESOPAL product contribution	Points
Ŷ	MR Materials and Resources	Building Product Disclosure and Optimi- zation - Environmental Product Declarations	Option 1 Environmental Product Declaration (EPD) - Product with conforming life cycle analysis	1 pt
		Building Product Disclosure and Optimization - Sourcing of Raw Materials	Option 2 Leadership extraction practice - Product made from PEFC or FSC®certified wood	1 pt
		Building Product Disclosure and Optimization - Material Ingredients	Option 3 Material ingredient optimization - Chemically inert material	1 pt
	EQ Indoor Environmental Quality	Low-Emitting Materials	Option 1 Product category calculations or Option 2 Budget calculation method - Product respecting TVOC and formaldehyde emission thresholds	Up to 3 pts
		Interior Lighting	Option 2 Lighting quality - Product eases natural lighting	1 pt



MR - Materials and Resources

Criterion	Requirem	ent - RESOPAL product contribution - Documentation				
Building Product Disclosure and Optimization -	USE A CERTAIN NUMBER OF PRODUCTS WITH AN ENVIRONMENTAL PRODUCT DECLARATION IN COMPLIANCE WITH THE REFERENCE CRITERIA.					
Environmental Product Declarations Option 1 Environmental Product Declaration (EPD)	1 pt	 Product with conforming life cycle analysis Indirect influence: RESOPAL has carried out Life Cycle Analysis (LCA) for RESOPAL Compact in compliance with the DIN EN 15804:2012+A2:2019 standard on environmental product declarations. Environmental Product Declaration (EPD) - EN Environmental Product Declaration (EPD) - background information - EN 				
	USE A CERTAIN NUMBER OF PRODUCTS FROM RESPONSIBLE SUPPLY SOURCES.					
Building Product Disclosure and Optimization - Sourcing of Raw Materials Option 2 Leadership extraction practice	1 pt	Product made from PEFC or FSC® certified wood Direct influence: RESOPAL Compact fulfils the criteria for responsible sourcing: All our products can be either PEFC (PEFC/04-31-1353) or FSC® (TSUD-COC-001239 and TSUD-CW-001239) certified on request, guaranteeing that the wood and raw materials used come from sustainably and responsibly managed forests (depending on the certification of ou suppliers, while stocks last). • PEFC-Certificate - EN • FSC®-Certificate - EN • Declaration European Timber Regulation (EUTR) - EN				
	USE A CERTAIN NUMBER OF PRODUCTS WITH PRE-EVALUATED COMPONENTS.					
Building Product Disclosure and Optimization - Material Ingredients Option 3 Material ingredient optimization	1 pt	 Chemically inert material Direct influence: RESOPAL Compact 0% urea formaldehyde 0% heavy metals including mercury, cadmium, lead and antimony 0% heavalent chromium and other regulated substances in compliance with the European Directive 2011/65/EU (EU RoHS) 0% pentachlorophenol 0% protective products (e.g. lacquer, varnish, etc.) As for all its products, RESOPAL Compact contains no chemical substances included in the candidate list of Substances of Very High Concern - SVHC - in concentrations higher than 0.1% of the mass. In addition, RESOPAL Compact has very low VOC emissions. Certificate of conformity RESOPAL HPL and RESOPAL Compact composition - DE - EN RESOPAL declaration - REACH regulation - EN Declaration of conformity ROHS - DE - EN 				

EQ - Indoor Environmental Quality



Criterion	Requirement - RESOPAL product contribution - Documentation								
	RESPECT THE STANDARD METHOD V1.1-2010 F REQUIREMENTS FOR THE WALL / CEILING CLADDING PRODUCTS.								
		Product respecting TVOC and formaldehyde emission thresholds Direct influence: RESOPAL Compact is a low-emitting material confirmed by a third-party testing institute. RESOPAL Compact complies with the strictest requirements in terms of indoor air quality, in accordance with the emissions criteria used by the United States Environmental Protection Agency (EPA), the State of California, the German Blue Angel (Blauer Engel) certification and other internationally known public health agencies.							
			Regulation	туос		Formaldehyde			
				MAXIMUM CONCENTRATIONS (µg/m³) - MEASURED AFTER 28 DAYS					
				limit	value	limit	value		
		RESOPAL Compact WALL SCENARIO	ABG/AgBB	≤ 1000	< 5	≤ 100	24		
Low-Emitting Materials Option 1	Up to 3 pts	RESOPAL TRACELESS PREMIUM Compact ALL SCENARIOS	ABG/AgBB	≤ 1000	< 5	≤ 100	< 3		
Product category calculations		RESOPAL Compact DOOR SCENARIO	ABG/AgBB	≤ 1000	< 5	≤ 100	< 3		
			Classification	TVOC Formaldehyde					
				ا MAXIMUM CONCENTRATIONS (µg/m³) - MEASURED AFTER 28 DAYS			-		
				limit	value	limit	value		
		RESOPAL Compact WALL SCENARIO	А	< 1500	< 2	< 60	24		
		RESOPAL TRACELESS PREMIUM Compact ALL SCENARIOS	A+	< 1000	< 2	< 10	< 3		
		RESOPAL Compact DOOR SCENARIO	A+	< 1000	< 2	< 10	< 3		
		 VOC Emission test report - Wall - RESOPAL HPL - EN VOC Emission test report - Door - RESOPAL HPL - EN VOC Emission test report - Wall - RESOPAL HPL Traceless Premium - EN 							
	CHOOSE 4 OF THE 8 SOLUTIONS AVAILABLE THAT GUARANTEE QUALITY LIGHTING.								
Interior Lighting Option 2 Lighting quality	1 pt	Product eases natural lighting Indirect influence: The daylight factor calculation takes account of different factors including the light reflectance value of floors, walls and ceilings. With its large range of over 300 decors (plain, wood, materials), RESOPAL Compact contributes to obtaining excellent daylight factor percentages: Its light reflectance values range from 0.06 for the 0901 Black decor to 0.85 for the 9417 Snow White decor.							
		Data Sheet - Surface Gloss and Surface	Brightness - EN						

Download all documentation proofs here



RESOPAL GmbH | Hans-Böckler-Straße 4 | 64823 Gross-Umstadt, Germany | **www.resopal.de** EN - Building Environmental Data Sheet - © Resopal GmbH- RE-002 - 01/2023

